

Light Weight 12v Taxi LED Display P5mm With 140° Viewing Angle

Our Product Introduction

for more products please visit us on hdled-display.com

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-SD P5
- Minimum Order Quantity: 1 pcs
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 10 days



Product Specification

- Product Name: P5 Outdoor Full Color Advertising Display
- Pixel Pitch: 5mm
- Pixel Configuration: 1R1G1B/SMD2727
- Density: 40,000 Pixel/m²
- Module Size(L×W)mm: 320mm×160mm
- Module Resolution: 64×32
- Driving Method: 1/8 Scan
- Driving IC: MBI5124 Or ICN 2038S
- Brightness: 6000cd/
- Contrast: 1000:1
- Highlight: taxi top digital signage,
taxi rooftop advertising signs



Product Description

P5mm taxi roof top signs for advertising , 12v led taxi display

Description:

1. Well Designed Cooling Syetem
2. Aliminum Casting with ultra thin,light weight design
3. Easy maintenance& IP65 design&long Lasting Display
4. Organized internal wire harnessing
5. Powerful control software
6. Supports flash,picture,video and text
7. High Speed data Transferring
8. A variety of connection mode, real-time information publish.

Remote Control

Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)

P5 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	5mm
Pixel Configuration	1R1G1B/SMD2727
Density	40,000 pixel/m2
Moduel Size(L×W)mm	320mm×160mm
Cabinet Size(L×W×H)mm	960mm×960mm×130mm
Module Resolution	64×32
Cabinet Resolution	192×192
Driving Method	1/8 Scan
Driving IC	MBI5124 or ICN 2038S
Brightness	6000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 750W
	Average power: 225W
Module Weight	0.28kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65
	Storage : -40 - 85
Environment Temperature	-30 to 60 ; humidity Rh10% to 95%
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 85-264V

Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)
------------	---

Our service

1. Your inquiry related to our products or price will be replied in 2hrs
2. OEM customized products
3. 2 years warranty
4. Complaint respond period not exceed 24 hours; maintenance guidance and problem solution supplied in 48 hours.
- 5.Free technician training..
- 6.Top quality+Reasonable price+Responsible After Service=Successful & Win

Competitive Advantage:

- 1, Good quality;
- 2, Good price;
- 3, Good 24hours service;
- 4, Promote delivery;
- 5, Energy-saving;
- 6, Small order accepted.



Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,
Shenzhen, China