

## P3.91 Stage LED Screens Indoor Full Color LED Display 9500K - 11500K

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD 3.91
- Minimum Order Quantity: 1 Sq.m
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 15 working days
- Supply Ability: 3000 Sq.m / month



### Product Specification

- Product Name: Stage LED Screens
- Pixel Configuration: 1R1G1B/SMD2121 Black Lamp
- Density: 65,536 Pixel/m<sup>2</sup>
- Module Size(L×W)mm: 250mm×250mm
- Cabinet Size(L×W×H)mm: 500mm×500mm×90mm
- Driving IC: MBI5124 Or ICN 2038S
- Brightness: 1000cd/
- Contrast: 1000:1
- Highlight: stage led display, stage background led screen



for more products please visit us on [hdled-display.com](http://hdled-display.com)

## Product Description

### Stage LED Screens P3.91 Indoor Full color LED Display

#### Description:

Set up parameter  
Brightness, grey scale, contrast ration, temperature parameter set up function.

System extension function  
Video camera, HD camera, DVD, can be introduced into the system.

The led display system has some protection functions of anti-high temperature, Anti-corrosion, pest control, waterproof, dust-proof, lightning protection, anti-static, wind, earthquake, anti-jamming systems.

#### Application:

It is wildly used in indoor scheduling command center ,public security ,military command center system ,monitoring security center ,video and television medio and other places of different indoor and outdoor hd display requirements.It's the best creative LED large screen system you're looking for.

### P3.91 Indoor Full color LED Display Specification

NO:	Product Name	Specification
1	Pixel Pitch	3.91mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	65,536 pixel/m2
4	Module Size(LxW)mm	250mmx250mm
5	Cabinet Size(LxWxH)mm	500mmx500mmx90mm
6	Module Resolution	64x64
7	Cabinet Resolution	128x128
8	Driving Method	1/16 Scan
9	Driving IC	MBI5124 or ICN 2038S
10	Brightness	1000cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 600W
14		Average power: 200W
15	Module Weight	0.52kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	160°
18	Vertical Viewing Angle	120°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024x1024x1024 16834x16834x16834
21	Control Distance	cable100m,Multimode500m,Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
26		Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65
30		Storage : -40 - 85
31	Environment Temperature	-30 to 60 ; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)

33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V
36	Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

#### Our service

1. Your inquiry related to our products or price will be replied in 2hrs
2. OEM customized products
3. 2 years warranty
4. Complaint respond period not exceed 24 hours; maintenance guidance and problem solution supplied in 48 hours.
5. Free technician training..
6. Top quality+Reasonable price+Responsible After Service=Successful & Win



**Vegoo** 威固电子 Shenzhen Weigu Electronic Technology Co., Ltd.

☎ 86-15118043086    ✉ Linda@vegooled.com    🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China