

Super Light Stage LED Screens 3.91mm Video Wall Led Display Noiseless

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD 3.91
- Minimum Order Quantity: 1 Sq.m
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 15 working days
- Supply Ability: 3000 Sq.m / month



Product Specification

- Product Name: Stage LED Screens
- Pixel Pitch: 3.91mm
- Density: 65,536 Pixel/m²
- Cabinet Resolution: 128×128
- Driving Method: 1/16 Scan
- Driving IC: MBI5124 Or ICN 2038S
- Brightness: 1000cd/
- Contrast: 1000:1
- Highlight: **stage led video wall,
stage background led screen**



for more products please visit us on hdled-display.com

Product Description

Super Light and Thin Noiseless Stage LED Screens 3.91mm

Description:

1. Super Light and Thin

0.52KG/panel with a depth of 90mm which is half of the depth of traditional LED screen, saving space and transportation cost.

2. High Refresh Rate

Refresh Rate \geq 1000, offering impressive visual effect.

3. Noiseless

Free of fans and air conditions, excluding noise and reducing power consumption.

P3.91 Indoor Full color LED Display Specification

NO:	Product Name	Specification
1	Pixel Pitch	3.91mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	65,536 pixel/m ²
4	Module Size(L×W)mm	250mm×250mm
5	Cabinet Size(L×W×H)mm	500mm×500mm×90mm
6	Module Resolution	64×64
7	Cabinet Resolution	128×128
8	Driving Method	1/16 Scan
9	Driving IC	MBI5124 or ICN 2038S
10	Brightness	1000cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 600W
14		Average power: 200W
15	Module Weight	0.52kg
16	Color Temperature	9500K—11500K
17	Horizontal Viewing Angle	160°
18	Vertical Viewing Angle	120°
19	Signal Processing	10 or 14bit
20	Grey Processing	1024×1024×1024 16834×16834×16834
21	Control Distance	cable100m, Multimode500m, Single mode 2km
22	Frame Frequency	65 Hz
23	Refresh Rate	>1920Hz
24	Control Mode	Synchronous/Asynchronous
25		With Eight Optional Gamma Calibration Curve
26	The Opposite Calibration Curve	Users can choose the recommended curve or adjust it based on actual situation
27	MTBF	>50000 hours
28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65 °C
30		Storage : -40 - 85 °C
31	Environment Temperature	-30°C to 60°C; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT, Windows2000, WindowsXP, Windows7
35	Power Supply	AC 110-220V

36	Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)
----	------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------

Customer Service

- 1) Guarantee Time: Within one year after delivery form factory
 - 2) Maintenance Coverage : LED modules,Power supply ,Control system and other accessories (This warranty exclude accessories purchasing form other factory)
 - 3) Maintenance Mode :
- By returned maintenance , through express or by other way
- 4) Response time for maintenance :

1. Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user;

2. Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours;

3. On-site mode: (only for user inside china) after receiving maintenance request , we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions , problems could be solved on the basis of friendly negotiation between two parties.



Vegoo 威固电子 Shenzhen Weigu Electronic Technology Co., Ltd.

☎ 86-15118043086

✉ Linda@vegooled.com

🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District , Shenzhen, China