

## Anticorrosion Smoulderproof 4mm Indoor Led Display Screen With Auto Brightness

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-RD 4
- Minimum Order Quantity: 1 sq.m
- Packaging Details: Flight case
- Delivery Time: 10-15 days
- Supply Ability: 3000sq.m/month



### Product Specification

- Product Name: P4 Indoor Full Color LED Display
- Pixel Pitch: 4mm
- Pixel Configuration: 1R1G1B/SMD2121 Black Lamp
- Moduel Size(L×W)mm: 256mm×128mm
- Brightness: 1000cd/
- Contrast: 1000:1
- Highlight: stage rental led display,  
outdoor rental led display



for more products please visit us on [hdled-display.com](http://hdled-display.com)

## Product Description

### Auto Brightness P4 Indoor Full color LED Display 9500K—11500K

#### Description:

From traditional LED products applications to irregular shape LED designs, from thematic LED applications to interactive multimedia integration, Linso is always at the cutting-edge of the industry. Our service covers the whole range of customer needs, from preliminary advice and planning, right through design and manufacturer to after-sales service and maintenance - with strict quality controls throughout.

The Linso service package is greatly enhanced by the company's long experience of providing complete LED solutions to a world-wide client base.

#### P4 Indoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	4mm
Pixel Configuration	1R1G1B/SMD2121 Black lamp
Density	62,500 pixel/m <sup>2</sup>
Module Size(L×W)mm	256mm×128mm
Cabinet Size(L×W×H)mm	512mm×512mm×90mm
Module Resolution	64×32
Cabinet Resolution	128×128
Driving Method	1/16 Scan
Driving IC	MBI5124 or ICN 2038S
Brightness	1000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 610W
	Average power: 240W
Module Weight	0.2kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65
	Storage : -40 - 85
Environment Temperature	-30 to 60 ; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 110–220V
Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)



**Vegoo** 威固电子 **Shenzhen Weigu Electronic Technology Co., Ltd.**

☎ 86-15118043086

✉ Linda@vegooled.com

🌐 hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China