



Basic Information

Place of Origin: ChinaBrand Name: Vegoo

Certification: CE/ROHS/FCC/
Model Number: VG-RD 3.91
Minimum Order Quantity: 1 sq.m
Packaging Details: Flight case
Delivery Time: 10-15 days
Supply Ability: 3000sq.m/month



Product Specification

Product Name:
 P3.91 Outdoor Full Color LED Display

Pixel Configuration: 1R1G1B/SMD2525Density: 65,536 Pixel/m2

• Cabinet Size(L×W×H)mm: 500mm×1000mm×90mm

Brightness: 4500cd/Contrast: 1000:1

 Highlight: stage rental led display, outdoor rental led display



Product Description

high refresh rate P3.91 Outdoor Full color LED Display 4500cd/

Description:

- 1) Super good pixels
- 2) super good refresh rate
- 3) Digital gray-scale technology
- 4) Energy-saving design cycle
- 5) Very good heat dissipation system
- 6) Light weight, can be customized color

Using Range:

Widely used in a variety of needs large hall, sports arena, banking, telecommunications, government agencies, terminal. pier, railway stations, the stock market and other trading market, medical systems, electric power, galleries and other publicity, advertising, information dissemination, the guise places

P3.91 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	3.91mm
Pixel Configuration	1R1G1B/SMD2525
Density	65,536 pixel/m2
Moduel Size(L×W)mm	250mm×250mm
Cabinet Size(L×W×H)mm	500mm×500mm×90mm
Module Resolution	64×64
Cabinet Resolution	128×128
Driving Method	1/16 Scan
Driving IC	MBI5124
Brightness	4500cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 480W
	Average power: 150W
Module Weight	0.663kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140º
Vertical Viewing Angle	140º
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65
	Storage : -40 - 85
Environment Temperature	-30 to 60 ; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7

Power Supply	AC 110-220V
Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Customer Service

- 1) Guarantee Time: Within one year after delivery form factory
- 2) Maintenance Coverage: LED modules, Power supply, Control system and other accessories (This warranty exclude accessories purchasing form other factory)
- 3) Maintenance Mode:
- By returned maintenance , through express or by other way
- 4) Response time for maintenance: Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user; Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours; On-site mode: (only for user inside china) after receiving maintenance request, we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions, problems could be solved on the basis of friendly negotiation between two parties.





Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com