

High Brightness P5.95 Rental LED Display 2 Years Warranty 28235 Pixel/M2

Basic Information

Place of Origin: ChinaBrand Name: Vegoo

Certification: CE/ROHS/FCC/
Model Number: VG-RD 5.95
Minimum Order Quantity: 1 sq.m
Packaging Details: Flight case
Delivery Time: 10-15 days
Supply Ability: 3000sq.m/month



Product Specification

Product Name:
 P5.95 Outdoor Full Color LED Display

• Pixel Pitch: 5.95mm

Pixel Configuration: 1R1G1B/SMD2727
 Density: 28,235 Pixel/m2
 Moduel Size(L×W)mm: 250mm×250mm

• Cabinet Size(L×W×H)mm: 500mm×500mm×90mm

Brightness: 6000cd/Contrast: 1000:1

 Highlight: stage rental led display, outdoor rental led display



Product Description

P5.95 Outdoor Full color Rental LED Display 28,235 pixel/m2

Description:

- 1. Clear picture without flicker and distortion
- 2. Multiform file formats, such as VGA, Video, AVI, MOV, MPG, DAT, VOB and so on are comprehensive
- 3. Low consumption, stable performance, highly durable
- 4. High brightness & broad viewing angle, brightness can be adjusted automatically or manually
- 5. 2 years warranty, easy to install & maintenance
- 6. CE, ROHS, FCC,

P5.95 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	5.95mm
Pixel Configuration	1R1G1B/SMD2727
Density	28,235 pixel/m2
Moduel Size(L×W)mm	250mm×250mm
Cabinet Size(L×W×H)mm	500mm×500mm×90mm
Module Resolution	42×42
Cabinet Resolution	84×84
Driving Method	1/7 Scan
Driving IC	MBI5124
Brightness	6000cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 600W
	Average power: 300W
Module Weight	0.72kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140º
Vertical Viewing Angle	140º
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024
Control Distance	16834×16834×16834 cable100m,Multimode500m,Single mode 2km
	-
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65
	Storage : -40 - 85
Environment Temperature	-30 to 60 ; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 110-220V

Protection

waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Service and Guarantees

Services Before-sale:Set a special telephone line to resolve the confusion from clients and supply free technology services by telephone. Consider the demands of clients carefully, study the situation of the installation condition. Team up the related staff and workers promptly, give clients design program details to help them choose the products which they wanted as soon as possible

Service In - sales :Try the best to meet the reasonable demands by clients Provisional changed .Keep close touch with the clients during the period if installation .Cooperate friendly with the clients, satisfy the clients with the best quality of led display .

Service After-sale:Normal products have one year guarantee, and whole life maintenance, free charges . we just charge materials cost only if products out off guarantee. You can down load and upgrade the related operating software of Led display freely from our company website, so as to resolve the problems when you use our led display. Check the quality of appliance, do maintenance job and ask good suggestions form clients on a regular time schedule .





Shenzhen Weigu Electronic Technology Co., Ltd.



86-15118043086



Linda@vegooled.com



hdled-display.com