



## Light Weight Curve P10 Outdoor Full Color LED Display Module 7500cd/

### Our Product Introduction


#### Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-FD P10
- Packaging Details: Plywood case / Flight case / Carton box
- Delivery Time: 3-5 days
- Supply Ability: 3000Sq.m



#### Product Specification

- Product Name: P10 Outdoor Full Color LED Display
- Pixel Pitch: 10mm
- Pixel Configuration: 1R1G1B/DIP 346
- Density: 10,000 Pixel/m<sup>2</sup>
- Cabinet Size(L×W×H)mm: 960mm×960mm×130mm
- Cabinet Resolution: 96×96
- Driving IC: MBI5124
- Contrast: 1000:1
- Highlight: outdoor advertising led display screen,  
outdoor full color led screen



## Product Description

### Light weight curve P10 Outdoor Full color LED Display 7500cd/

#### Description:

LED display with its light weight (12.8 kg) and wide application possibilities. The portable, waterproof I-Magic takes only 10 seconds to assemble. Its main advantages include:

- Light weight and slim design
- Easy and fast installation and maintenance
- Waterproof, wind resistant and great heat dissipation
- Indoor and outdoor screens are compatible with each other
- Can be used for any stage application
- Floor LED display can bear 1 ton weight
- Hanging, pile-up and fix installation available

#### P10 Outdoor Full color LED Display Specification

Product Name	Specification
Pixel Pitch	10mm
Pixel Configuration	1R1G1B/DIP 346
Density	10,000 pixel/m <sup>2</sup>
Module Size(L×W)mm	320mm×160mm or 160mm×160mm
Cabinet Size(L×W×H)mm	960mm×960mm×130mm
Module Resolution	32×16
Cabinet Resolution	96×96
Driving Method	1/ 4 Scan
Driving IC	MBI5124
Brightness	7500cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 850W
	Average power: 340W
Module Weight	0.5kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve
	Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65
	Storage : -40 - 85
Environment Temperature	-30 to 60 ; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)

Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 110-220V
Protection	waterproof, dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)



#### Customer Service

- 1) Guarantee Time: Within one year after delivery form factory
- 2) Maintenance Coverage : LED modules,Power supply ,Control system and other accessories ( This warranty exclude accessories purchasing form other factory )
- 3) Maintenance Mode :  
By returned maintenance , through express or by other way
- 4) Response time for maintenance :
  1. Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user;
  2. Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours;
  3. On-site mode: ( only for user inside china ) after receiving maintenance request , we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions , problems could be solved on the basis of friendly negotiation between two parties.

**Vegoo** 威固电子 **Shenzhen Weigu Electronic Technology Co., Ltd.**



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,  
Shenzhen, China