

High Contrast 3.91mm Rental LED Display Wall Exhibition Outdoor 1000:1

Our Product Introduction

Basic Information

- Place of Origin: Made in China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/
- Model Number: VG-RD-P3.91-500-1
- Minimum Order Quantity: 1 sq.m
- Packaging Details: Flight case
- Delivery Time: 15-20 days
- Supply Ability: 3000sq.m/month



Product Specification

- Product Name: Rental LED Display
- Pixel Pitch: 3.91mm
- Pixel Configuration: 1R1G1B/SMD2121 Black Lamp
- Density: 65,536 Pixel/m²
- Moduel Size(L×W)mm: 250mm×250mm
- Contrast: 1000:1
- Material: Nation Star SMD2020
- Usage: Indoor Portable
- Application: Exhibition Outdoor
- Material: Die Casting Aluminum
- Highlight: **stage rental led display, led video wall rental**

for more products please visit us on hdled-display.com

Product Description

High Contrast 3.91mm Rental LED Display Wall Exhibition Outdoor 1000:1

Rental LED Display Features & benefits

1. High brightness: Above 5500 nits/sq.m
2. High Refresh Rate: $\geq 1920\text{Hz}$, Take clear picture with mobile phone
3. Ultra Thin Design: the thickness of cabinet with backdoor is only 12cm
4. Fast and easy to assemble: There have fast lock between cabinet side

Rental LED Display Application:

Rental LED Display widely used for stage, events, live broadcasting etc.


Rental LED Display Specification

No	Product Name	Specification
1	Pixel Pitch	3.91mm
2	Pixel Configuration	1R1G1B/SMD2121 Black lamp
3	Density	65,536 pixel/m ²
4	Module Size(L×W)mm	250mm×250mm
5	Cabinet Size(L×W×H)mm	500mm×1000mm×90mm
6	Module Resolution	64×64
7	Cabinet Resolution	128×256
8	Driving Method	1/16 Scan
9	Driving IC	MBI5124 or ICN 2038S
10	Brightness	1000cd/
11	Contrast	1000:1
12	Brightness Adjustment	Auto and Manual
13	Power Consumption	Max Power: 600W Average power: 200W
14	Module Weight	0.52kg
15	Color Temperature	9500K—11500K
16	Horizontal Viewing Angle	160°
17	Vertical Viewing Angle	120°
18	Signal Processing	10 or 14bit
19	Grey Processing	1024×1024×1024 16834×16834×16834
20	Control Distance	cable100m, Multimode500m, Single mode 2km
21	Frame Frequency	65 Hz
22	Refresh Rate	>1920Hz
23	Control Mode	Synchronous/Asynchronous
24	The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve Users can choose the recommended curve or adjust it based on actual situation
25	MTBF	>50000 hours

28	Life Span	100,000 Hours
29	Operating Temperature	Working : -20 - 65
30		Storage : -40 - 85
31	Environment Temperature	-30 to 60 ; humidity Rh10% to 95%
32	Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
33	Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)
34	Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
35	Power Supply	AC 110-220V
36	Protection	dustproof, high temperature pervention, anticorrosion, smoulderproof, anti-static, shockproof, lightningproof, smoke alarm and temperature alarm. (Be customized)

Service and Guarantees

Services Before-sale: Set a special telephone line to resolve the confusion from clients and supply free technology services by telephone. Consider the demands of clients carefully, study the situation of the installation condition, Team up the related staff and workers promptly, give clients design program details to help them choose the products which they wanted as soon as possible

 **Shenzhen Weigu Electronic Technology Co., Ltd.**

 86-15118043086  Linda@vegooled.com  hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District, Shenzhen, China