

## Removable RGB SMD 6mm Rental LED Display For Stages

Our Product Introduction

for more products please visit us on [hdled-display.com](http://hdled-display.com)

### Basic Information

- Place of Origin: China
- Brand Name: Vegoo
- Certification: CE/ROHS/FCC/CCC
- Model Number: VG-SUN88823
- Minimum Order Quantity: Negotiation
- Price: Negotiable
- Packaging Details: Flight case,plywood box,carton
- Delivery Time: 10-25 days
- Payment Terms: L/C, T/T
- Supply Ability: 3000sq.m/month




### Product Specification

- Product Name: Rental LED Display
- Pixel Pitch: 6mm
- Module Size(L×W)mm: 192×192
- Material: Aluminum Or Iron
- Feature: High Resolution
- Brightness: 6500cd/
- Highlight: 6mm rental led display screen,  
SMD led backdrop screen rental



### More Images



## Product Description

### Easy Installation Removable Rental RGB LED Display SMD Full Color Panel For Stages

#### Our core advantage:

1. Compatible with multiple functions:VGA, Video, AVI, MOV, MPG, DAT, VOB and so on.
2. Clear picture show without flicker and distortion.
3. Brightness, contrast and saturation can be adjusted automatically or manual.
4. Display content with your PC synchronously.
5. Customized for indoor or outdoor use,the pixel pitch is optional.

#### Rental LED Display Specification

Product Name	Rental LED Display
Pixel Pitch	6mm
Pixel Configuration	1R1G1B/SMD3535
Density	27,777 pixel/m2
Module Size(L×W)mm	192mm×192mm
Cabinet Size(L×W×H)mm	576mm×576mm×90mm
Module Resolution	32×32
Cabinet Resolution	96×96
Driving Method	1/8 Scan
Driving IC	MBI5124
Brightness	6500cd/
Contrast	1000:1
Brightness Adjustment	Auto and Manual
Power Consumption	Max Power: 545W Average power: 165W
Module Weight	0.244kg
Color Temperature	9500K—11500K
Horizontal Viewing Angle	140°
Vertical Viewing Angle	140°
Signal Processing	10 or 14bit
Grey Processing	1024×1024×1024 16834×16834×16834
Control Distance	cable100m,Multimode500m,Single mode 2km
Frame Frequency	65 Hz
Refresh Rate	>1920Hz
Control Mode	Synchronous/Asynchronous
The Opposite Calibration Curve	With Eight Optional Gamma Calibration Curve Users can choose the recommended curve or adjust it based on actual situation
MTBF	>50000 hours
Life Span	100,000 Hours
Operating Temperature	Working : -20 - 65 Storage : -40 - 85
Environment Temperature	-30 to 60 ; humidity Rh10% to 95%
Remote Control	Can realize remote control and send alarm signal to operators in case of logging failure (Be customized)
Self-checking Technique	Self-inspection, communication test, power test, temperature monitoring (Be customized)

Operating System Platform	WindowsNT,Windows2000,WindowsXP,Windows7
Power Supply	AC 110-220V



### Customer Service

- 1) Guarantee Time: Within one year after delivery form factory
- 2) Maintenance Coverage : LED modules,Power supply ,Control system and other accessories ( This warranty exclude accessories purchasing form other factory )
- 3) Maintenance Mode :  
By returned maintenance , through express or by other way
- 4) Response time for maintenance :  
Return mode: after receiving the returned products, we will repaired them within 24 hours and send them back to the user;  
Telephone or internet mode: we will contact user within 2 hours after getting informations and give solution within 8 hours;  
On-site mode: ( only for user inside china ) after receiving maintenance request , we will respond within 48 hours to user in Guangdong province; 72 hours to user outside Guangdong province, In the case of some special conditions , problems could be solved on the basis of friendly negotiation between two parties.



86-15118043086



Linda@vegooled.com



hdled-display.com

806 Building 1 Geya Technology Building, Clock Base, Ma Tou community, Ma Tian Street, Guangming District ,  
Shenzhen, China